

## Pigment for tinting of plasters.

07 01 20

Mineral pigments are intended for SAKRET mineral decorative plasters SBP and MRP. Pigments can also be used for tinting other mineral mortars.

**Application:**

- For interior and exterior works
- For wall decoration
- By using tinted mineral decorative plaster, you can combine plaster pulling and painting in one operation.

**Suitability:**

- For coloured concretes
- For the production of masonry, cement and lime paints
- All types of cement and lime binders for building materials

**Qualities:**

- Resistant to UV radiation
- Cost effective system
- Pigments are of inorganic origin, which ensures long-lasting tones in any climate
- In construction, it is possible to combine two operations - plastering and painting
- Contains no solvents

**Components:**

- Mineral pigment
- Fillers

**Technical data:**

Aggregate state	Powder type
Colour	130 – red; 920 – yellow 375 – black; 01 – green 686 – brown; 4960 - orange
pH	3,5-8
Solubility (in water), +20°C	Forms emulsion

**Foundation preparation:**

Before applying plaster, the surface must be primed with SAKRET PG primer. The base must be dry, firm and without cracks. Clean the base from less durable and/or separable layers, as well as from dust, dirt, oils, paint residues, etc. adhesion-reducing dirt.

To ensure even surface colouring, pay attention to the amount of pigment and water to be added to one bag - one container of pigment is intended for one bag (25 kg) of Sakret decorative plaster or mortar. Use exactly the same amount of water for each subsequent bag.

**Processing:**

- Add 4/5 parts warm water to the pigment.
- Close the container and shake it thoroughly until the pigment is evenly dissolved in the water
- The entire pigment solution is added to the water intended for the preparation of the decorative coating
- Add SAKRET dry plaster mix
- Mix the plaster thoroughly, wait 10 min. And mix again
- Apply the decorative plaster on a previously primed surface (in the case of dark tones, we recommend tinting the primer)
- Processing temperature +5°C to +25°C

**Additional recommendations for processing:**

- If the plaster mortar starts to bind during work, do not add water, but mix again.
- When applying the decorative plaster, you should try to cover the entire surface in one pass. If this is not possible, make connections with painter's tape. A freely formed joint between the plaster applied at different times will be easily visible later.
- Wash tools with water immediately after work is finished

## Pigment for tinting of plasters.

07 01 20

<b>Consumption:</b>	<ul style="list-style-type: none"> <li>One container of pigment is intended for one bag (25 kg) of SAKRET decorative plaster (SBP or MRP).</li> </ul>
<b>Packing:</b>	<ul style="list-style-type: none"> <li>PE cup 0.5 l/ box 24 pcs. / Full pallet 576 pcs.</li> </ul>
<b>Storage:</b>	<ul style="list-style-type: none"> <li>Duration of storage in original, unopened packaging – 48 months</li> <li>Store at a temperature of +5°C to +30°C</li> </ul>
<b>Utilization:</b>	<ul style="list-style-type: none"> <li>Dispose of the packaging in accordance with the requirements of local legislation.</li> </ul>
<b>Safety information:</b>	<ul style="list-style-type: none"> <li>Safety phrases are listed on the packaging and safety data sheets.</li> </ul>
<b>Additional information:</b>	<ul style="list-style-type: none"> <li>Plaster and colour pigments are of mineral origin, so their tone will change during drying depending on the drying conditions.</li> <li>Protect fresh plaster from rain and too rapid drying, avoid direct sunlight during processing.</li> <li>Technical data refer to temperature +23±2°C and relative air humidity 50±5%.</li> </ul>

Colour code	Packing 1	Packing 2	Barcode
130-1	200 g	576 pcs. / Pallet	4751006561182
130-2	200 g	576 pcs. / Pallet	4751006561199
130-3	200 g	576 pcs. / Pallet	4751006561205
686-1	200 g	576 pcs. / Pallet	4751006561212
686-2	200 g	576 pcs. / Pallet	4751006561229
686-3	200 g	576 pcs. / Pallet	4751006561236
920-1	200 g	576 pcs. / Pallet	4751006561243
920-2	200 g	576 pcs. / Pallet	4751006561250
920-3	200 g	576 pcs. / Pallet	4751006561267
4960-1	200 g	576 pcs. / Pallet	4751006561274
4960-2	200 g	576 pcs. / Pallet	4751006561281
4960-3	200 g	576 pcs. / Pallet	4751006561298
375-1	200 g	576 pcs. / Pallet	4751006561304
375-2	200 g	576 pcs. / Pallet	4751006561311
375-3	200 g	576 pcs. / Pallet	4751006561328
01-1	200 g	576 pcs. / Pallet	4751006561335
01-2	200 g	576 pcs. / Pallet	4751006561342
01-3	200 g	576 pcs. / Pallet	4751006561359

The information provided in the technical data sheet is based on laboratory tests and practical experience. The manufacturer is not responsible for damages caused by improper use of the given product. In case of questions and uncertainties, please contact the manufacturer or seller. Information about the safety of the product is available in the safety data sheets, declared values – in declaration of performance.