TECHNICAL DATA SHEET



SAND 0-2 MM

15 09 16

Sand fraction 0-2 mm for production of building mortars.

Application:	 As a fine filler for production of mortars and concrete. As a joint filler for pavement slabs. 		
	For filtration layer.		
	For creation of levelling layers.		
	For street anti-slip sprinkling.		
	For sandboxes.		
	• For flower pots.		
	For aquariums.		
Components:	Natural sand – washe	d, dried, fractioned, does no	contain clay and dust particles.
Technical data:	Parameter	Value	Category
	Granulometric content	0-2 mm	Gf 85
	Fines content (<0,063mr	n) ≤3%	F3
	Roughness model	2,81,5	MF
	Bulk density	1,50-1,60 kg /	dm ³ -
	Organic impurities	no	-
	Humidity	< 0,2%	-
	 mixer, mix with cold, clear water until homogenous mixture of needed consistency without lumps is formed and start processing. Recommendable binders for preparation of construction mortars and concrete: sand ratio is from 1:3 till 1:5. 		
Packing:	 Paper bags 25 kg / full pallet 48 pcs. 1000 kg / Big bag / pre-ordered 		
Storage:	 Packing must be kept away from impact of weather conditions, store on wooden pallets in cool and dry place, torn or opened packing must be covered immediately. Storage time in original unopened packing – unlimited. 		
Utilization:	 Hardened mixture shall be utilized in compliance with local legislation as construction material of mineral origin. Packing shall be utilized in compliance with local legislation demands. 		
Safety information:		cking and in safety data she	
Paint	Packing 1	Packing 2	Barcode
Brown	25 kg	48 pcs./ Pallet	4751006562448

The information provided in the technical data sheet refers to the usage of the above product, if there is no other technical documentation, prepared and issued by the producer. The producer is not responsible for losses caused by wrong usage of the given product. In case of questions or uncertainty, please contact producer or seller. Information on product's safety is available in safety data sheets, declared values – in declaration of performance.