



SAKRET ECONOM Water dispersion acrylic primer for interior works

15 08 21

Water dispersion acrylic primer for interior decoration work

Application:

- For residential and public premises;
- For priming of walls and ceiling, before painting with water dispersion paints, except silicate paint.

Suitability:

- For painting of new and previously painted surfaces;
- For concrete surfaces;
- For plastered surfaces;
- For brick surfaces;
- For filled surfaces;
- For gyps cardboards;
- For wooden-fiber plates;
- For surfaces covered with colorable wallpapers.

Qualities:

- Ecologically clean;
- Improves surface adhesion;
- Evens surface absorption capacity;
- Decreases paint's consumption;
- Not runny;
- Financially advantageous.

Components:

- Acrylic copolymer dispersion;
- White pigment;
- Inert fillers;
- Technological additives.

Technical data:	Tone	White
	Solvent	Water
	Gloss	Completely matted
	Drying time at 23°C and relative air humidity 50%	Surface can be painted after 2 h
	Density, g/cm ³	1,38 – 1,42
	Viscosity, P (Brookfield, LV4, 50rpm)	40 - 80
	Solids content, %	52

Foundation preparation:

- Paintable surface must be firm and dry (surface humidity ≤ 2%).
- Not previously painted surfaces must be cleaned off dirt, fat and dust.
- Previously painted surfaces must be cleaned off peeled paint. Weakly bounded surface must be cleaned off till firm foundation and then it shall be prepared the same as fresh surface.
- Surface, previously painted with shiny color shall be evenly grinded and grinding dust must be cleaned off.
- Fill, if necessary.

Processing:

- Primer shall be mixed properly before usage.
- Primer is ready for usage.
- Using sprayer for priming, the primer can be diluted with water (till 10% of the amount), if necessary.
- Prime with roller, brush or sprayer (nozzle 0,015" - 0,021").



SAKRET ECONOM

**Water dispersion acrylic primer
for interior works**

15 08 21

Additional recommendations for application:	<ul style="list-style-type: none"> • The surface to be primed and air temperature during priming and drying time must be from +7°C till +25°C (recommended +18±2°C), and relative air humidity not more than 80%. • If the temperature is too high or draught persists, imperfect membrane may appear. • Tools shall be washed with water, straight after work is finished.
Consumption:	<ul style="list-style-type: none"> • 8 – 15 m²/l; • Consumption depends on surface roughness and porosity as well as painting method and conditions.
Packing:	<ul style="list-style-type: none"> • PP bucket 10 l / full pallet 33 pcs.
Storage:	<ul style="list-style-type: none"> • Storage time in original, closed packing – 24 months. • Store in temperature +5°C till +30°C. • Protect from frost!
Utilization:	<ul style="list-style-type: none"> • Packing shall be utilized in compliance with local legislation demands.
Safety information:	<ul style="list-style-type: none"> • Safety phrases are on packing and in safety data sheets. • Permissible VOC content (sub-group A/a) 30 g/l. Maximum VOC content in product 7 g/l.
Additional information:	<ul style="list-style-type: none"> • Technical data refer to temperature +23±2°C and relative air humidity 50±5%

Paint (base)	Packing 1	Packing 2	Barcode
White	10 l	33 pcs./pallet	4751006563001

The information provided in the technical data sheet is based on laboratory tests and practical experience. The producer is not responsible for losses caused by wrong usage of the given product. In case of questions or uncertainty, please contact producer or seller. Information on product's safety is available in safety data sheets, declared values – in declaration of performance.