



SAKRET PROF Complete matt acrylic paint for interior works 15 08 21

Complete matte water dispersion acrylic paint for interior decoration work

- Application:**
- For less loaded surfaces;
 - For residential and public premises;
 - For painting of walls and ceiling in dry premises.

- Suitability:**
- For painting of new and previously painted surfaces;
 - For concrete surfaces;
 - For plastered surfaces;
 - For brick surfaces;
 - For filled surfaces;
 - For gyps cardboard plates;
 - For wooden-fibre plates;
 - For colourable wallpapers surfaces.

- Quality:**
- Ecologically clean;
 - Complete matte;
 - Priming not needed;
 - Can be tinted in light tones, tone precision is not absolute;
 - Good coverage;
 - Not runny;
 - Financially advantageous.

- Components:**
- Acrylic copolymer dispersion;
 - Pigments;
 - Inert fillers;
 - Technological additives.

Technical data:

Tone	White, can be tinted in light tones
Solvent	Water
Gloss	Complete matte
Wet-scrub resistance (ISO 11998/EN 13300)	62 µm (28 days, 40 cycles), class 4
Washing resistance (SFS 3755)	Resists more than 700 washing cycles
Drying time at 23°C and relative air humidity 50%	Surface can be painted repeatedly after 3 h
Density, g/cm ³	1,35 – 1,40
Viscosity, P (Brookfield, LV4, 50rpm)	40 - 80
Solids content, %	52

- Foundation preparation:**
- Paintable surface must be firm and dry (surface humidity ≤ 2%).
 - Not previously painted surfaces must be cleaned off dirt, fat and dust.
 - Previously painted surfaces must be cleaned off peeled paint. Weakly bounded surface must be cleaned off till firm foundation and then prepared the same as fresh surface.
 - Surface, previously painted with shiny colour shall be evenly grinded and grinding dust must be cleaned off.
 - Fill, if necessary



SAKRET PROF Complete matt acrylic paint for interior works 15 08 21

Processing:	<ul style="list-style-type: none"> • Paint shall be mixed properly before use; • Paint is ready for use; • Covering first paint layer on surface as well as using sprayer for painting, the paint can be diluted with water (till 10% of the amount), if necessary. • The finishing layer surface is covered with undiluted paint. • Paint with roller, brush or sprayer (nozzle 0,015"- 0,021") 2 layers. • Ceiling shall be painted in light incidence direction.
Additional recommendations for application:	<ul style="list-style-type: none"> • The colourable surface and air temperature during painting and drying time must be from +7°C till +25°C (recommended +18±2°C), and relative air humidity not more than 80%. • If the temperature is too high or draught persists, imperfect membrane may appear. • Tools shall be washed with water straight after work is finished.
Consumption:	<ul style="list-style-type: none"> • 7 – 9 m²/l covering in one layer; • Consumption depends on surface roughness and porosity as well as painting method and conditions.
Packing:	<ul style="list-style-type: none"> • PP bucket 10 l / full pallet 33 pcs.
Storage:	<ul style="list-style-type: none"> • Storage time in original, closed packing – 24 months. • Store in temperature +5°C till +30°C. • Protect from frost!
Utilization:	<ul style="list-style-type: none"> • Packing shall be utilized in compliance with local legislation demands.
Safety information:	<ul style="list-style-type: none"> • Safety phrases are on packing and in safety data sheets. • Permissible VOC content (sub-group A/a) 30 g/l. Maximum VOC content in product 1 g/l.
Additional information:	<ul style="list-style-type: none"> • Technical data refer to temperature +23±2°C and relative air humidity 50±5%.

Paint (base)	Packing 1	Packing 2	Barcode
White	10 l	33 pcs./ pal.	4751006562585

The information provided in the technical data sheet is based on laboratory tests and practical experience. The producer is not responsible for losses caused by wrong usage of the given product. In case of questions or uncertainty, please contact producer or seller. Information on product's safety is available in safety data sheets, declared values – in declaration of performance.