



SAKRET FR Protective material against fungi and algae

15 08 21

Material for processing of surfaces before painting or other decoration, to protect from fungi and algae.

- Application:**
- For exterior works;
 - For interior works.

- Suitability:**
- Masonry, concrete, plastered, brick and other material surfaces can be processed;
 - Can be used to process production facilities with increased hygiene demands.
 - Recommended for pre-treatment in thermal insulation works.
 - Do not use to wash oil stains or other impurities of organic origin.

- Qualities:**
- Effective means against formation of fungi and algae colonies.
 - Processed surface after drying can be painted without washing.
 - No special skills are needed when using this product.

- Components:**
- Demineralized water solution with biocide.

Technical data:	Shape	Colourless liquid
	Density, g/cm ³	1,00
	pH	6 - 8

- Foundation preparation:**
- Surface must be firm and dry before processing.
 - Dirty and dusty surfaces must be cleaned and rinsed with high pressure washer.
 - Rinsed surfaces must be properly dried before processing.

- Processing:**
- Apply the liquid on surface with roller, paintbrush or sprayer in such amount that the surface can absorb.
 - After drying the surface can be painted, plastered, decoration and other construction works.

- Additional recommendations for application:**
- The surface and air temperature should be not less than +5°C.
 - Do not work during rain or strong wind.
 - It is not necessary to wash tools, because after drying they are ready for further use. If tools have become dirty after contact with processed surface, they must be washed with water.

- Consumption:**
- Consumption depends on surface roughness and porosity as well as priming method and conditions.
 - Concrete, lime/cement plaster SAKRET CLP+ - 3-5 m²/l;
 - Clay brick – 12-14 m²/l;
 - Mineral decorative plaster SAKRET SBP 2 mm – 2-4 m²/l;
 - Expanded clay concrete blocks – 1,5-3 m²/l;

- Packing:**
- PP bottle 1 l / 15 pcs. in box / full pallet 360 pcs.;
 - PP can 5 l / full pallet 72 pcs.
 - PP can 10 l / full pallet 36 pcs.

- Storage:**
- Storage time in original, closed packing – 36 months.
 - Store in temperature +5°C till +30°C;
 - **Protect from frost!**

- Utilization:**
- Packing shall be utilized in compliance with local legislation demands.

- Safety information:**
- Safety phrases are on packing and in safety data sheets.

**SAKRET FR****Protective material against fungi and algae**

15 08 21

Additional information:

- Technical data refer to temperature +23±2°C and relative air humidity 50±5%.

Paint (base)	Packing 1	Packing 2	Barcode
	1 l	360 pcs. /pal.	4751006564640
	5 l	72 pcs. /pal.	4751006564305
	10 l	36 pcs. /pal.	4751006564312

The information provided in the technical data sheet is based on laboratory tests and practical experience. The producer is not responsible for losses caused by wrong usage of the given product. In case of questions or uncertainty, please contact producer or seller. Information on product's safety is available in safety data sheets, declared values – in declaration of performance.